

Taxitronic TX52 taximeter is able to offer you each and every one of the features you look for in a taximeter: simplicity, robustness, reliability and with built-in printer. Designed and designed to integrate naturally in the interior of your vehicle.





Capacity for 32 complete and independent rates



With BG40, Linked by Bluetooth with the Android Smart TD



Basic system of up to 10 turns and driver control



Thermal printer with Easy Loading system



Display and printing of totes, anti-theft secret code...



Includes support designed to orient the equipment three-dimensionally



Optional Module for Time Control



Automatic rate changes by time, distance, amount, hour, day...



■ TECHNICAL FEATURES ■

| Power Supply Voltage | Nominal: 12 V Máxima: 16 V Mínima: 8 V |
|---|--|
| Maximum consumption with meter in OFF | 5mA |
| Maximum consumption without exterior lights | 450mA |
| Consumption Peaks during Ticket Printing | Up to 1,5A |
| Maximum internal battery consumption | 5 mA |
| Operating temperature | -10°C to +70°C |
| Storage temperature | -40°C to +85°C |
| Device constant K | 400 to 80,000 pulses per km/ml |

■ MECHANICAL FEATURES ■

| Dimensions | 180mm wide x 50mm high x 50mm deep |
|-------------------------|--|
| Bracket | Adjustable height and vertical and horizontal tilt |
| Dimensions with Bracket | 150mm wide x 70mm high x 50mm deep |
| Weight | 300 gr |

■ CERTIFICATIONS / REGULATIONS

| 2004/22/CE | Directive 2004/22 / EC of the European Parliament and of the Council of 31 March 2004 on measuring instruments |
|-------------|---|
| 2004/I08/CE | Directive 2004/108 / EC of the European Parliament and of the Council of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility |

